

— L350 —

PREMIUM ACRYLIC CURE TECHNICAL DATA SHEET

Rev. 03-03-2020



Performance

- UV stable (non-yellowing)
- Stain resistant (oil, grease, drinks, etc.)
- Meets or exceeds ASTM C-1315 and ASTM C-309
- Retains moisture in new concrete for a proper stronger cure
- Protects from discoloration or color loss
- Long lasting and durable
- Easy to apply
- Quick dry time
- Cost effective
- Low VOC (<350 g/L)

25% PREMIUM ACRYLIC CURING COMPOUND

DESCRIPTION

ACP L350 Premium Acrylic Cure is a high performing, solvent-based, non-yellowing, low VOC, acrylic copolymer for curing, hardening, and sealing new or existing concrete. This premium formula is made with the highest quality ingredients from around the globe that produce an impervious, durable film that will retain moisture for freshly placed concrete, ensuring an optimal strength development as the concrete cures. This premium copolymer also doubles as a decorative concrete sealer with a beautiful high gloss “wet look” finish. L350 is a proprietary formula utilizing special additives and premium acrylic resins to deliver exceptionally high quality at an affordable price.

NOTES BEFORE APPLYING

- Test cure and seal in an inconspicuous area to ensure desired results are achieved.
- More porous surfaces may require more coats to achieve desired gloss finish.
- Do not apply too thick to avoid product failure.
- Make sure concrete surface is completely dry.
- Avoid contact with skin, eyes, and clothing.

Technical Data

Chemistry:	Acrylic
Applications:	Concrete, New Concrete, Stone
Color:	Clear
Finish:	High Gloss
Coverage:	200-300 sq. ft. per gallon
Application Method:	Sprayer/Roller
Application Temp:	60°F-90°F
Number of Coats:	1 (2 for high gloss)
Recoat Time:	1 - 3 hours
Solvent/Water:	Solvent
Full Cure:	12 - 24 hours
Packaging:	1 Gallon, 5 Gallon, 55 Gallon
Interior/Exterior:	Interior/Exterior
New Concrete:	After water slurry Absorbs
VOC Content:	348 g/L
Clean up/Removal:	Xylene
Shelf Life:	Best if used within 1 year

APPLICATION

L350 Premium Acrylic Cure was developed as a curing compound for fresh concrete by retaining moisture as the concrete cures. L350 is also optimal as a high gloss sealer for stamped concrete, pavers, curbing, stone, and other cementitious substrates. For optimal performance, please follow the application process. Please refer to the Safety Data Sheet (SDS) before using.

- For curing applications, after all surface water or slurry has absorbed into the concrete, spray a thin even layer on the surface with an Acetone Resistant sprayer. Applying product too thick can result in product failure.
- Concrete must be clean of all dirt, oil, grease, wax, paints, previous sealers, and other contaminants that might impede penetration of the product.
- Concrete must be completely dry. Wait for at least 24-48 hours after rain or if concrete was washed with water.
- If acid is used to wash concrete, make sure acid is neutralized with soap and water. Rinse completely and wait 24-48 hours to dry.
- Cover all surrounding surfaces and areas where product is not wanted.
- When rolling L350, use a good quality 3/8" nap roller. Pour product into a paint tray, dip roller in the tray, and apply a thin coat evenly over surface. Applying product too thick can result in entrapment and cause bubbles, white spots, or other product failure.
- For highest gloss results, two coats are recommended. Wait 1-3 hours between coats to ensure the first coat is completely dry. Generally, L350 is dry and ready for another coat if it does not feel "sticky" when touched with your hand. In colder temperatures, more time will be required for product to dry and be ready for another coat.
- Let sealer dry for 4-6 hours before foot traffic and 12-24 hours before driving. Keep dry from water for 24-48 hours.

LIMITATIONS OF LIABILITY

The information supplied by us and this Technical Data Sheet is accurate to the best of our knowledge. Our products are manufactured to the highest quality control and expectations although no warranty is made for any particular purpose. The information provided is intended to be a guide and it is recommended that you conduct your own tests to determine whether or not this product is suitable for your particular application. The information listed is compiled from typical conditions and should not be considered a guarantee or warranty. We are not liable for any damages, incidental or consequential, involving this product or its user. Any liability, refund or replacement will be at our full discretion and will be taken on a case by case basis. Acceptance of delivery of our product means you accept these terms described. It should also be noted that ACP products contain chemicals that may cause serious injury. Read the Safety Data Sheet (SDS) carefully before using.